



Frutteto³ CLASSIC

The perfect combination of versatility and comfort.

SDF 1000 Series 3 or 4 cylinder engine, Tier3 specification, turbo or turbo-intercooled, available in 2WD and 4WD versions. With its compact dimensions, extreme strength and supreme manoeuvrability, the SAME Frutteto³ Classic is ideal for specialty crop cultivation. A fold-down roll bar and tight steering angle combine to maximize agility, but without jeopardizing productivity and safety. And thanks to its structural design, the Frutteto³ Classic will be a real asset for tillage duties too



FRUTTETO ³ CLASSIC		60	70	80	80.4	90	100
ENGINE							
Emissions		Tier3	Tier3	Tier3	Tier3	Tier3	Tier3
Manufacturer		SDF	SDF	SDF	SDF	SDF	SDF
Cylinders/Capacity	No./cm ³	3/3,000	3/3,000	3/3,000	4/4,000	4/4,000	4/4,000
Intake		Turbo Intercooler	Turbo Intercooler	Turbo Intercooler	Turbo Intercooler	Turbo Intercooler	Turbo Intercooler
Max. power	kW/HP	45,5/62	53/72	60/82	58,8/80	62,5/85	70/95
Power at rated engine speed	kW/HP	45,5/62	53/72	60/82	55/75	62,5/85	70/95
Max. torque at 1,600 rpm	Nm	240	265	310	325	345	373
Electronic engine management		•	•	•	•	•	•
Fuel tank capacity	litres	55	55	55	55	55	55
SHUTTLE							
Synchronised mechanical reverse shuttle		•	•	•	•	•	•
MECHANICAL GEARBOX							
5 speed gearbox		•	•	•	•	•	•
Number of speeds with underdrive	n°	20 + 10	20 + 10	20 + 10	20 + 10	20 + 10	20 + 10
Number of speeds with underdrive and supercreeper gear	n°	30 + 15	30 + 15	30 + 15	30 + 15	30 + 15	30 + 15
REAR P.T.O.							
Mechanical engagement		•	•	•	•	•	•
PTO 540		○	○	○	○	○	○
PTO 540/540ECO		•	•	•	•	•	•
PTO 540/540ECO/1000		○	○	○	○	○	○
Ground speed PTO		○	○	○	○	○	○
FRONT AND REAR AXLE							
Four wheel drive mechanically engaged		•	•	•	•	•	•
Differential lock mechanically engaged		•	•	•	•	•	•
BRAKES AND STEERING							
Multi-disc wet brakes on all four wheels		•	•	•	•	•	•
Independent parking brake		•	•	•	•	•	•
Hydraulic trailer braking		○	○	○	○	○	○
Hydrostatic steering with independent pump		•	•	•	•	•	•
Steering angle	degrees	60°	60°	60°	60°	60°	60°
LIFT							
Mechanical rear lift		•	•	•	•	•	•
Rear lift capacity	kg	2,600	2,600	2,600	2,800	2,800	2,800
HYDRAULIC SYSTEM							
Pump output	l/min	45	45	45	45	45	45
Rear hydraulic auxiliary distributors	No. of ways	4 / 6	4 / 6	4 / 6	4 / 6	4 / 6	4 / 6
PLATFORM							
Semi-platform		•	•	•	•	•	•
Digital display		•	•	•	•	•	•
Safety frame		•	•	•	•	•	•
Driving seat mechanically adjustable		•	•	•	•	•	•
DIMENSIONS AND WEIGHTS							
Standard rear tyres		360/70R24	360/70R24	380/70R24	360/70R24	360/70R24	420/70R28
Max. length without rear linkage	mm	3,186	3,186	3,208	3,338	3,338	3,338
Width (min./max.)	mm	1,514 / 2,012	1,588 / 1,988	1,514 / 2,012	1,588 / 1,988	1,588 / 1,988	1,588 / 1,988
Max height at ROPS	mm	2,228	2,250	2,250	2,380	2,380	2,380
Ground clearance	mm	270	270	270	270	270	270
Wheelbase	mm	1,990	1,990	1,990	2,120	2,120	2,120
Front track (min./max.)	mm	1,166 / 1,442	1,166 / 1,442	1,166 / 1,442	1,166 / 1,442	1,166 / 1,442	1,296 / 1,496
Rear track (min./max.)	mm	1,091 / 1,491	1,091 / 1,491	1,051 / 1,545	1,091 / 1,491	1,091 / 1,491	1,185 / 1,585
Turning circle	mm	3,600	3,600	3,600	3,700	3,700	3,700
Max. weight with ROPS	kg	2,500	2,500	2,500	2,650	2,650	2,650
Maximum load capacity	kg	5,000	5,000	5,000	5,000	5,000	5,000

• STD ○ OPT - Not available

Dealer

same-tractors.com

The use of original SDF lubricants and coolants is recommended.

SAME is a brand of  SDF

